

Rostfritt

Rundstång

Rostfri dragen alt. slipad rundstång enligt EN 1088/EN 10278, tolerans enligt ISO h9, i fabriktionslängder om 3 - 6 m.

Dimension	Vikt kg/m	EN 1.4301	EN 1.4305	EN 1.4404
YD				
5	0,16	X		
5	0,16		X	
6	0,22	X		
6	0,22		X	
8	0,40	X		
8	0,40		X	
8	0,40			X
10	0,62	X		
10	0,62		X	
10	0,62			X
12	0,89	X		
12	0,89		X	
12	0,89			X
14	1,21	X		
14	1,21		X	
15	1,42	X		
15	1,42		X	
16	1,58	X		
16	1,58		X	
16	1,58			X
18	2,00	X		
18	2,00		X	
20	2,47	X		
20	2,47		X	
20	2,47			X

Dimension	Vikt kg/m	EN 1.4301	EN 1.4305	EN 1.4404
YD				
22	2,98	X		
22	2,98		X	
25	3,85	X		
25	3,85		X	
25	3,85			X
30	5,55	X		
30	5,55		X	
30	5,55			X
35	7,60	X		
35	7,60		X	
40	9,92	X		
40	9,92		X	
40	9,92			X
45	12,56	X		
45	12,56		X	
50	15,50	X		
50	15,50		X	
50	15,50			X
60	22,32	X		
60	22,32		X	