

Sömlösa rör

ASTM A312/TP316L

Sömlösa rostfria rör enligt ANSI B 36.19, stålsort ASTM A312 TP316L, i fabriktionslängder 4 - 8 m, släta ändar, märkta med chargennummer. Verkscertifikat enligt EN 10204/3.1.

Dimension mm	Dimension tum	Vikt kg/m
RSÖ13,7 x 2,24	1/4" sch40s	0,65
RSÖ17,1 x 3,20	3/8" sch80s	1,12
RSÖ21,30 x 2,11	1/2" sch10s	1,02
RSÖ21,34 x 2,77	1/2" sch40s	1,29
RSÖ21,34 x 3,73	1/2" sch80s	1,65
RSÖ21,34 x 4,78	1/2" sch160	1,98
RSÖ26,67 x 2,11	3/4" sch10s	1,30
RSÖ26,67 x 2,87	3/4" sch40s	1,71
RSÖ26,67 x 3,91	3/4" sch80s	2,23
RSÖ26,67 x 5,56	3/4" sch160	2,94
RSÖ33,40 x 2,77	1" sch10s	2,13
RSÖ33,40 x 3,38	1" sch40s	2,54
RSÖ33,40 x 4,55	1" sch80s	3,29
RSÖ48,26 x 2,77	1.1/2" sch10s	3,16
RSÖ48,26 x 3,68	1.1/2" sch40s	4,11
RSÖ48,26 x 5,08	1.1/2" sch80s	5,49
RSÖ60,33 x 2,77	2" sch10s	3,99
RSÖ60,33 x 3,91	2" sch40s	5,52
RSÖ60,33 x 5,54	2" sch80s	7,60
RSÖ88,90 x 3,05	3" sch10s	6,56
RSÖ88,90 x 5,49	3" sch40s	11,47
RSÖ114,30 x 3,05	4" sch10s	8,50
RSÖ114,30 x 6,02	4" sch40s	16,32
RSÖ168,28 x 3,40	6" sch10s	14,04
RSÖ168,28 x 7,11	6" sch40s	28,69