

Rostfritt

Svetsade fyrkantsrör

Svetsade rostfria fyrkantsrör, i fabriktionslängder om 6000 mm

-0/+100 mm. I borstat eller obehandlat utförande där annat ej anges.

| Dimension | | | Vikt Kg/m | Utförande | EN 1.4307 EN 1.4301 | EN 1.4404 | EN 1.4571 |
|-----------|----|------|--------------|-----------|------------------------|-----------|-----------|
| YD | YD | Gods | | | | | |
| 10 | 10 | 1,0 | 0,300 | | X | | |
| 15 | 15 | 1,0 | 0,463 | | X | | |
| 15 | 15 | 1,5 | 0,676 | K240/K320 | X | | |
| 15 | 15 | 1,5 | 0,676 | | X | | |
| 15 | 15 | 1,5 | 0,676 | K240/K320 | X | | |
| 20 | 10 | 1,2 | 0,538 | | X | | |
| 20 | 10 | 1,2 | 0,538 | K240/K320 | X | | |
| 20 | 10 | 1,5 | 0,676 | | X | | |
| 20 | 10 | 1,5 | 0,676 | K240/K320 | X | | |
| 20 | 15 | 1,5 | 0,798 | | X | | |
| 20 | 15 | 1,5 | 0,798 | K240/K320 | X | | |
| 20 | 20 | 1,0 | 0,626 | K240/K320 | X | | |
| 20 | 20 | 1,2 | 0,745 | | X | | |
| 20 | 20 | 1,2 | 0,745 | K240/K320 | X | | |
| 20 | 20 | 1,5 | 0,920 | | X | | |
| 20 | 20 | 1,5 | 0,920 | K240/K320 | X | | |
| 20 | 20 | 1,5 | 0,920 | | | | X |
| 20 | 20 | 2,0 | 1,202 | | X | | |
| 20 | 20 | 2,0 | 1,202 | K240/K320 | X | | |
| 20 | 20 | 2,0 | 1,202 | | | | X |
| 25 | 10 | 1,5 | 0,798 | | X | | |
| 25 | 10 | 1,5 | 0,798 | K240/K320 | X | | |
| 25 | 15 | 1,5 | 0,920 | | X | | |
| 25 | 15 | 1,5 | 0,920 | K240/K320 | X | | |
| 25 | 25 | 1,2 | 0,941 | K240/K320 | | | |
| 25 | 25 | 1,2 | 0,941 | | X | | |
| 25 | 25 | 1,2 | 0,941 | K240/K320 | X | | |
| 25 | 25 | 1,5 | 1,164 | | X | | |
| 25 | 25 | 1,5 | 1,164 | K240/K320 | X | | |
| 25 | 25 | 1,5 | 1,164 | | | | X |
| 25 | 25 | 2,0 | 1,527 | | X | | |
| 25 | 25 | 2,0 | 1,527 | K240/K320 | X | | |
| 25 | 25 | 2,0 | 1,527 | | | | X |
| 25 | 25 | 3,0 | 2,216 | | X | | |
| 30 | 10 | 1,5 | 0,920 | | X | | |
| 30 | 10 | 1,5 | 0,920 | K240/K320 | X | | |
| 30 | 15 | 1,2 | 0,825 | | X | | |
| 30 | 15 | 1,2 | 0,825 | K240/K320 | X | | |
| 30 | 15 | 1,5 | 1,042 | | X | | |
| 30 | 15 | 1,5 | 1,042 | K240/K320 | X | | |
| 30 | 15 | 1,5 | 1,042 | | | | X |
| 30 | 15 | 2,0 | 1,365 | | X | | |
| 30 | 15 | 2,0 | 1,365 | K240/K320 | X | | |
| 30 | 20 | 1,2 | 0,921 | K240/K320 | X | | |

| Dimension | | | Vikt Kg/m | Utförande | EN 1.4307 EN 1.4301 | EN 1.4404 | EN 1.4571 |
|-----------|----|------|--------------|-----------|------------------------|-----------|-----------|
| YD | YD | Gods | | | | | |
| 30 | 20 | 1,2 | 0,921 | K240/K320 | X | | |
| 30 | 20 | 1,5 | 1,164 | | X | | |
| 30 | 20 | 1,5 | 1,164 | K240/K320 | X | | |
| 30 | 20 | 2,0 | 1,527 | | X | | |
| 30 | 20 | 2,0 | 1,527 | K240/K320 | X | | |
| 30 | 20 | 2,0 | 1,527 | | | | X |
| 30 | 30 | 1,2 | 1,136 | K240/K320 | X | | |
| 30 | 30 | 1,2 | 1,136 | | X | | |
| 30 | 30 | 1,5 | 1,409 | | X | | |
| 30 | 30 | 1,5 | 1,409 | K240/K320 | X | | |
| 30 | 30 | 1,5 | 1,409 | | | | X |
| 30 | 30 | 2,0 | 1,853 | | X | | |
| 30 | 30 | 2,0 | 1,853 | K240/K320 | X | | |
| 30 | 30 | 2,0 | 1,853 | | | | X |
| 30 | 30 | 3,0 | 2,704 | | X | | |
| 30 | 30 | 3,0 | 2,704 | K240/K320 | X | | |
| 30 | 30 | 3,0 | 2,704 | | | | X |
| 35 | 20 | 1,5 | 1,259 | | X | | |
| 35 | 35 | 1,2 | 1,303 | | X | | |
| 35 | 35 | 1,2 | 1,303 | K240/K320 | X | | |
| 35 | 35 | 1,5 | 1,653 | | X | | |
| 35 | 35 | 1,5 | 1,653 | K240/K320 | X | | |
| 35 | 35 | 2,0 | 2,178 | K240/K320 | X | | |
| 35 | 35 | 2,0 | 2,178 | | X | | |
| 35 | 35 | 2,0 | 2,178 | | | | X |
| 35 | 35 | 3,0 | 3,193 | | X | | |
| 40 | 15 | 1,5 | 1,286 | | X | | |
| 40 | 20 | 1,2 | 1,136 | | X | | |
| 40 | 20 | 1,2 | 1,136 | K240/K320 | X | | |
| 40 | 20 | 1,5 | 1,409 | | X | | |
| 40 | 20 | 1,5 | 1,409 | K240/K320 | X | | |
| 40 | 20 | 2,0 | 1,853 | | X | | |
| 40 | 20 | 2,0 | 1,853 | K240/K320 | X | | |
| 40 | 20 | 2,0 | 1,853 | | | | X |
| 40 | 20 | 3,0 | 2,650 | | X | | |
| 40 | 27 | 1,5 | 1,536 | | X | | |
| 40 | 30 | 1,2 | 1,303 | K240/K320 | X | | |
| 40 | 30 | 1,5 | 1,653 | | X | | |
| 40 | 30 | 1,5 | 1,653 | K240/K320 | X | | |
| 40 | 30 | 2,0 | 2,178 | | X | | |
| 40 | 30 | 2,0 | 2,178 | K240/K320 | X | | |
| 40 | 30 | 2,0 | 2,178 | | | | X |
| 40 | 30 | 3,0 | 3,193 | | X | | |
| 40 | 40 | 1,0 | 1,243 | K240/K320 | X | | |
| 40 | 40 | 1,0 | 1,243 | | X | | |
| 40 | 40 | 1,2 | 1,526 | | X | | |
| 40 | 40 | 1,2 | 1,526 | K240/K320 | X | | |
| 40 | 40 | 1,3 | 1,544 | | X | | |
| 40 | 40 | 1,3 | 1,544 | K240/K320 | X | | |
| 40 | 40 | 1,5 | 1,897 | K240/K320 | X | | |
| 40 | 40 | 1,5 | 1,897 | | X | | |
| 40 | 40 | 2,0 | 2,504 | | X | | |
| 40 | 40 | 2,0 | 2,504 | K240/K320 | X | | |
| 40 | 40 | 2,0 | 2,504 | | | | X |

| Dimension | | | Vikt Kg/m | Utförande | EN 1.4307 EN 1.4301 | EN 1.4404 | EN 1.4571 |
|-----------|----|------|--------------|-----------|------------------------|-----------|-----------|
| YD | YD | Gods | | | | | |
| 40 | 40 | 3,0 | 3,681 | | X | | |
| 40 | 40 | 3,0 | 3,681 | | | X | |
| 40 | 40 | 3,0 | 3,681 | K240/K320 | X | | |
| 40 | 40 | 3,0 | 3,681 | | | | X |
| 40 | 40 | 4,0 | 4,808 | | X | | |
| 40 | 40 | 4,0 | 4,808 | | | | X |
| 45 | 45 | 2,0 | 2,830 | | X | | |
| 45 | 45 | 2,0 | 2,830 | K240/K320 | X | | |
| 50 | 20 | 1,5 | 1,653 | | X | | |
| 50 | 20 | 1,5 | 1,653 | K240/K320 | X | | |
| 50 | 20 | 2,0 | 2,178 | | X | | |
| 50 | 20 | 2,0 | 2,178 | K240/K320 | X | | |
| 50 | 20 | 2,0 | 2,178 | | | | X |
| 50 | 25 | 1,5 | 1,775 | | X | | |
| 50 | 25 | 1,5 | 1,775 | K240/K320 | X | | |
| 50 | 25 | 1,5 | 1,775 | | | | X |
| 50 | 25 | 2,0 | 2,341 | K240/K320 | X | | |
| 50 | 25 | 2,0 | 2,341 | | X | | |
| 50 | 25 | 2,0 | 2,341 | | | | X |
| 50 | 30 | 1,5 | 1,897 | | X | | |
| 50 | 30 | 1,5 | 1,897 | K240/K320 | X | | |
| 50 | 30 | 1,5 | 1,897 | | | | X |
| 50 | 30 | 2,0 | 2,504 | | X | | |
| 50 | 30 | 2,0 | 2,504 | K240/K320 | X | | |
| 50 | 30 | 2,0 | 2,504 | | | | X |
| 50 | 30 | 3,0 | 3,681 | | X | | |
| 50 | 30 | 3,0 | 3,681 | K240/K320 | X | | |
| 50 | 30 | 3,0 | 3,681 | | | | X |
| 50 | 40 | 2,0 | 2,803 | | X | | |
| 50 | 40 | 2,0 | 2,803 | K240/K320 | X | | |
| 50 | 40 | 2,0 | 2,803 | | | | X |
| 50 | 40 | 3,0 | 4,169 | | X | | |
| 50 | 50 | 1,5 | 2,385 | | X | | |
| 50 | 50 | 1,5 | 2,385 | K240/K320 | X | | |
| 50 | 50 | 1,5 | 2,385 | | | | X |
| 50 | 50 | 2,0 | 3,155 | | X | | |
| 50 | 50 | 2,0 | 3,155 | K240/K320 | X | | |
| 50 | 50 | 2,0 | 3,155 | | | | X |
| 50 | 50 | 3,0 | 4,657 | | X | | |
| 50 | 50 | 3,0 | 4,657 | K240/K320 | X | | |
| 50 | 50 | 3,0 | 4,657 | | | | X |
| 50 | 50 | 4,0 | 6,110 | | X | | |
| 50 | 50 | 4,0 | 6,110 | K240/K320 | X | | |
| 50 | 50 | 4,0 | 6,110 | | | | X |
| 50 | 50 | 5,0 | 7,512 | | X | | |
| 60 | 20 | 1,5 | 1,897 | | X | | |
| 60 | 20 | 1,5 | 1,897 | K240/K320 | X | | |
| 60 | 20 | 2,0 | 2,504 | | X | | |
| 60 | 20 | 2,0 | 2,504 | K240/K320 | X | | |
| 60 | 20 | 2,0 | 2,504 | | | | X |
| 60 | 30 | 1,5 | 2,141 | | X | | |
| 60 | 30 | 1,5 | 2,141 | K240/K320 | X | | |
| 60 | 30 | 1,5 | 2,141 | | | | X |
| 60 | 30 | 2,0 | 2,830 | K240/K320 | X | | |
| 60 | 30 | 2,0 | 2,830 | | X | | |

| Dimension | | | Vikt Kg/m | Utförande | EN 1.4307 EN 1.4301 | EN 1.4404 | EN 1.4571 |
|-----------|----|------|--------------|-----------|------------------------|-----------|-----------|
| YD | YD | Gods | | | | | |
| 60 | 30 | 2,0 | 2,830 | | | | X |
| 60 | 30 | 3,0 | 4,169 | | X | | |
| 60 | 30 | 3,0 | 4,169 | K240/K320 | X | | |
| 60 | 30 | 3,0 | 4,169 | | | | X |
| 60 | 40 | 1,5 | 2,385 | | X | | |
| 60 | 40 | 2,0 | 3,155 | | X | | |
| 60 | 40 | 2,0 | 3,155 | K240/K320 | X | | |
| 60 | 40 | 2,0 | 3,155 | | | | X |
| 60 | 40 | 3,0 | 4,657 | | X | | |
| 60 | 40 | 3,0 | 4,657 | K240/K320 | X | | |
| 60 | 40 | 3,0 | 4,657 | | | | X |
| 60 | 40 | 4,0 | 6,110 | | X | | |
| 60 | 40 | 4,0 | 6,110 | | | | X |
| 60 | 60 | 1,5 | 2,873 | | X | | |
| 60 | 60 | 1,5 | 2,873 | K240/K320 | X | | |
| 60 | 60 | 2,0 | 3,806 | K240/K320 | X | | |
| 60 | 60 | 2,0 | 3,806 | | X | | |
| 60 | 60 | 2,0 | 3,806 | | | | X |
| 60 | 60 | 3,0 | 5,634 | | X | | |
| 60 | 60 | 3,0 | 5,634 | K240/K320 | X | | |
| 60 | 60 | 3,0 | 5,634 | | | | X |
| 60 | 60 | 4,0 | 7,412 | | X | | |
| 60 | 60 | 4,0 | 7,412 | K240/K320 | X | | |
| 60 | 60 | 4,0 | 7,412 | | | | X |
| 60 | 60 | 5,0 | 9,140 | | X | | |
| 60 | 60 | 5,0 | 9,140 | | | | X |
| 70 | 40 | 2,0 | 3,405 | | X | | |
| 70 | 40 | 3,0 | 5,146 | | X | | |
| 70 | 70 | 2,0 | 4,457 | | X | | |
| 70 | 70 | 3,0 | 6,611 | | X | | |
| 70 | 70 | 3,0 | 6,611 | | | | X |
| 70 | 70 | 4,0 | 8,714 | | X | | |
| 70 | 70 | 4,0 | 8,714 | | | | X |
| 70 | 70 | 5,0 | 10,767 | | X | | |
| 80 | 30 | 3,0 | 5,146 | | X | | |
| 80 | 40 | 1,5 | 2,873 | | X | | |
| 80 | 40 | 1,5 | 2,873 | K240/K320 | X | | |
| 80 | 40 | 2,0 | 3,806 | K240/K320 | X | | |
| 80 | 40 | 2,0 | 3,806 | | X | | |
| 80 | 40 | 2,0 | 3,806 | | | | X |
| 80 | 40 | 3,0 | 5,634 | | X | | |
| 80 | 40 | 3,0 | 5,634 | K240/K320 | X | | |
| 80 | 40 | 3,0 | 5,634 | | | | X |
| 80 | 40 | 4,0 | 7,412 | | X | | |
| 80 | 40 | 4,0 | 7,412 | | | | X |
| 80 | 40 | 5,0 | 9,140 | | X | | |
| 80 | 50 | 2,0 | 4,132 | | X | | |
| 80 | 50 | 3,0 | 6,122 | | X | | |
| 80 | 50 | 5,0 | 9,850 | | X | | |
| 80 | 60 | 2,0 | 4,557 | | X | | |
| 80 | 60 | 2,0 | 4,557 | | | | X |
| 80 | 60 | 3,0 | 6,611 | | X | | |
| 80 | 60 | 3,0 | 6,611 | K240/K320 | X | | |
| 80 | 60 | 3,0 | 6,611 | | | | X |
| 80 | 60 | 3,0 | 6,611 | | | | X |
| 80 | 60 | 4,0 | 8,714 | | X | | |

| Dimension | | | Vikt Kg/m | Utförande | EN 1.4307 EN 1.4301 | EN 1.4404 | EN 1.4571 |
|-----------|-----|------|--------------|-----------|------------------------|-----------|-----------|
| YD | YD | Gods | | | | | |
| 80 | 60 | 4,0 | 8,714 | | | | X |
| 80 | 60 | 5,0 | 10,540 | | X | | |
| 80 | 80 | 2,0 | 5,108 | | X | | |
| 80 | 80 | 2,0 | 5,108 | K240/K320 | X | | |
| 80 | 80 | 2,0 | 5,108 | | | | X |
| 80 | 80 | 3,0 | 7,587 | | X | | |
| 80 | 80 | 3,0 | 7,587 | K240/K320 | X | | |
| 80 | 80 | 3,0 | 7,587 | | | | X |
| 80 | 80 | 4,0 | 10,016 | | X | | |
| 80 | 80 | 4,0 | 10,016 | K240/K320 | X | | |
| 80 | 80 | 4,0 | 10,016 | | | | X |
| 80 | 80 | 5,0 | 12,395 | | X | | |
| 80 | 80 | 5,0 | 12,395 | | | | X |
| 80 | 80 | 6,0 | 14,724 | | X | | |
| 90 | 90 | 3,0 | 8,388 | | X | | |
| 90 | 90 | 4,0 | 11,050 | | X | | |
| 100 | 40 | 2,0 | 4,457 | | X | | |
| 100 | 40 | 2,0 | 4,457 | K240/K320 | X | | |
| 100 | 40 | 3,0 | 6,611 | | X | | |
| 100 | 40 | 3,0 | 6,611 | | | | X |
| 100 | 40 | 4,0 | 9,365 | | X | | |
| 100 | 40 | 4,0 | 9,365 | | | | X |
| 100 | 50 | 2,0 | 4,783 | | X | | |
| 100 | 50 | 2,0 | 4,783 | | | | X |
| 100 | 50 | 3,0 | 7,099 | | X | | |
| 100 | 50 | 3,0 | 7,099 | K240/K320 | X | | |
| 100 | 50 | 4,0 | 9,365 | | X | | |
| 100 | 50 | 4,0 | 9,365 | | | | X |
| 100 | 50 | 5,0 | 11,581 | | X | | |
| 100 | 50 | 5,0 | 11,581 | | | | X |
| 100 | 50 | 6,0 | 14,648 | | X | | |
| 100 | 60 | 2,0 | 5,108 | | X | | |
| 100 | 60 | 2,0 | 5,108 | | | | X |
| 100 | 60 | 3,0 | 7,587 | | X | | |
| 100 | 60 | 3,0 | 7,587 | K240/K320 | X | | |
| 100 | 60 | 4,0 | 10,016 | | X | | |
| 100 | 60 | 4,0 | 10,016 | K240/K320 | X | | |
| 100 | 60 | 4,0 | 10,016 | | | | X |
| 100 | 60 | 5,0 | 12,395 | | X | | |
| 100 | 60 | 5,0 | 12,395 | | | | X |
| 100 | 60 | 6,0 | 14,600 | | X | | |
| 100 | 80 | 3,0 | 8,564 | | X | | |
| 100 | 80 | 3,0 | 8,564 | | | | X |
| 100 | 80 | 4,0 | 11,318 | | X | | |
| 100 | 80 | 5,0 | 13,750 | | X | | |
| 100 | 100 | 2,0 | 6,410 | | X | | |
| 100 | 100 | 2,0 | 6,410 | K240/K320 | X | | |
| 100 | 100 | 2,0 | 6,410 | | | | X |
| 100 | 100 | 3,0 | 9,540 | | X | | |
| 100 | 100 | 3,0 | 9,540 | K240/K320 | X | | |
| 100 | 100 | 3,0 | 9,540 | | | | X |
| 100 | 100 | 4,0 | 12,620 | | X | | |
| 100 | 100 | 4,0 | 12,620 | | | | X |

| Dimension | | | Vikt Kg/m | Utförande | EN 1.4307 EN 1.4301 | EN 1.4404 | EN 1.4571 |
|-----------|-----|------|--------------|-----------|------------------------|-----------|-----------|
| YD | YD | Gods | | | | | |
| 100 | 100 | 5,0 | 15,650 | | | | X |
| 100 | 100 | 6,0 | 18,630 | | X | | |
| 100 | 100 | 6,0 | 18,630 | | | | X |
| 100 | 100 | 8,0 | 21,500 | | X | | |
| 120 | 40 | 2,0 | 5,108 | | X | | |
| 120 | 40 | 3,0 | 7,587 | K240/K320 | X | | |
| 120 | 40 | 3,0 | 7,587 | | X | | |
| 120 | 40 | 4,0 | 9,807 | | X | | |
| 120 | 60 | 2,0 | 5,759 | | X | | |
| 120 | 60 | 3,0 | 8,564 | | X | | |
| 120 | 60 | 3,0 | 8,564 | K240/K320 | X | | X |
| 120 | 60 | 3,0 | 8,564 | | | | X |
| 120 | 60 | 4,0 | 11,318 | | X | | |
| 120 | 60 | 4,0 | 11,318 | | | | X |
| 120 | 60 | 5,0 | 14,022 | | X | | |
| 120 | 60 | 5,0 | 14,022 | | | | X |
| 120 | 60 | 6,0 | 16,677 | | X | | |
| 120 | 80 | 2,0 | 6,410 | | X | | |
| 120 | 80 | 2,0 | 6,410 | K240/K320 | X | | |
| 120 | 80 | 3,0 | 9,540 | | X | | |
| 120 | 80 | 3,0 | 9,540 | K240/K320 | X | | X |
| 120 | 80 | 3,0 | 9,540 | | | | X |
| 120 | 80 | 4,0 | 12,620 | | X | | |
| 120 | 80 | 4,0 | 12,620 | | | | X |
| 120 | 80 | 5,0 | 15,650 | | X | | |
| 120 | 80 | 6,0 | 18,630 | | X | | |
| 120 | 120 | 2,0 | 7,555 | | X | | |
| 120 | 120 | 3,0 | 11,493 | | X | | |
| 120 | 120 | 3,0 | 11,493 | K240/K320 | X | | |
| 120 | 120 | 3,0 | 11,493 | | | | X |
| 120 | 120 | 4,0 | 15,224 | | X | | |
| 120 | 120 | 4,0 | 15,224 | | | | X |
| 120 | 120 | 5,0 | 18,905 | | X | | |
| 120 | 120 | 5,0 | 18,905 | | | | X |
| 120 | 120 | 6,0 | 22,536 | | X | | |
| 140 | 80 | 3,0 | 10,517 | | X | | |
| 140 | 80 | 4,0 | 13,922 | | X | | |
| 140 | 80 | 5,0 | 17,287 | | X | | |
| 140 | 140 | 5,0 | 21,120 | | X | | |
| 150 | 50 | 3,0 | 9,540 | | X | | |
| 150 | 50 | 3,0 | 9,540 | | | | X |
| 150 | 50 | 4,0 | 12,620 | | X | | |
| 150 | 50 | 5,0 | 15,650 | | X | | |
| 150 | 80 | 5,0 | 17,709 | | X | | |
| 150 | 100 | 3,0 | 11,982 | | X | | |
| 150 | 100 | 3,0 | 11,982 | | | | X |
| 150 | 100 | 4,0 | 15,875 | | X | | |
| 150 | 100 | 5,0 | 19,719 | | X | | |
| 150 | 100 | 6,0 | 23,513 | | X | | |
| 150 | 100 | 6,0 | 23,513 | | | | X |
| 150 | 100 | 10,0 | 33,650 | | X | | |
| 150 | 150 | 3,0 | 14,423 | | X | | |
| 150 | 150 | 4,0 | 19,131 | | X | | |
| 150 | 150 | 4,0 | 19,131 | | | | X |
| 150 | 150 | 5,0 | 23,788 | | X | | |

| Dimension | | | Vikt Kg/m | Utförande | EN 1.4307 EN 1.4301 | EN 1.4404 | EN 1.4571 |
|-----------|-----|------|--------------|-----------|------------------------|-----------|-----------|
| YD | YD | Gods | | | | | |
| 150 | 150 | 5,0 | 23,788 | | | | X |
| 150 | 150 | 6,0 | 28,359 | | X | | |
| 150 | 150 | 8,0 | 37,460 | | X | | |
| 160 | 80 | 3,0 | 11,493 | | X | | |
| 160 | 80 | 4,0 | 15,224 | | X | | |
| 160 | 80 | 5,0 | 18,905 | | X | | |
| 160 | 80 | 5,0 | 18,905 | | | | X |
| 200 | 100 | 3,0 | 14,423 | | X | | |
| 200 | 100 | 4,0 | 19,131 | | X | | |
| 200 | 100 | 5,0 | 23,788 | | X | | |
| 200 | 100 | 6,0 | 28,395 | | X | | |
| 200 | 150 | 4,0 | 21,400 | | X | | |
| 200 | 200 | 3,0 | 19,306 | | X | | |
| 200 | 200 | 4,0 | 25,641 | | X | | |
| 200 | 200 | 5,0 | 31,962 | | X | | |
| 200 | 200 | 6,0 | 38,161 | | X | | |
| 250 | 100 | 3,0 | 17,089 | | X | | |
| 250 | 100 | 4,0 | 22,386 | | X | | |
| 250 | 100 | 5,0 | 27,857 | | X | | |
| 250 | 100 | 8,0 | 40,700 | | X | | |
| 250 | 150 | 4,0 | 25,641 | | X | | |
| 250 | 150 | 5,0 | 30,962 | | X | | |
| 250 | 150 | 10,0 | 62,600 | | X | | |